



DESCRIÇÃO

010.2017

ESCOPO DA ENTREGA

RJ45 Cat. 6 connection module, unshielded, without mounting plate Dust cover Cable tie Installation instructions

CARACTERÍSTICAS

As part of a Cat. 6 channel, the connection module exceeds the minimum requirements of the IEEE 802.3™ Section Four standard on 10GBASE-T performance, as well as the requirements for Class EA performance acc. to ISO/IEC 11801 and Cat. 6A performance according to TIA 568.2-D Exceeds Cat.6 specifications acc. to ISO/IEC 11801, EN 50173 and TIA 568.2-D in the entire admissible range Maximum reliability through special contact design without internal transfer points Capacitive and inductive compensation 3P and UL certified

DADOS TÉCNICOS

DESCRIÇÃO	VALOR / GAMA DE VALORES
Category connector (A)	Cat. 6
Connector type (A)	RJ45
Shielding connector (A)	unshielded
PoE	Yes
Connector class	connection module
Wiring diagram	T568A and T568B
Holder for connector / module	Special (without mounting plate)
Poles	8
Standard	UL Listed EN 50173-1 IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801

DADOS MECÂNICOS

DESCRIÇÃO	VALOR / GAMA DE VALORES
Dimensions	14.0 mm x 21.5 mm x 41.0 mm / 0.551 in x 0.846 in x 1.614 in (W x H x D)
Color	blue
Material	plastic: PC, UL 94 V-0