



Blanking elements in black and white, for Keystone openings in Patch Panels



unilan® Patch Panel KS 24x - screened



## Product information

### Application

#### unilan® Patch Panel KS 24x (screened)

Screened patch panel to be used with up to 24 x KS 1/8 RJ45-Keystone Modules (Cat.6 or Cat.5).

Snap in modules are easily fitted into the patch panel.  
Unused ports can be covered with blanking elements.

### Description

Front cover made of flame retardant compound, UL94V-0 rated in combination with stainless steel and a cable strain relief.  
Frontview in grey, similar to RAL 7035 or in black, similar to RAL 9005.  
Modules are not part of the delivery.  
Strain relief with cable ties.

### Dimensions

Width	482 mm (19")
Depth	160 mm (including cable strain relief)
Height	44 mm (1U)

Article No.	Description	Colour (similar)	PU
418 019	unilan® Patch Panel KS 24x, 19" 1U , for 24x RJ45-Keystone Modules (FTP) (delivered without modules)	black RAL 9005	1 piece
418 020	unilan® Patch Panel KS 24x, 19" 1U , for 24x RJ45-Keystone Modules (FTP) (delivered without modules)	grey RAL 7035	1 piece

Article No.	Accessories/Description	Colour (similar)	PU
418 010	Blanking elements for Keystone Patch Panels	white	10 pieces
418 011	Blanking elements for Keystone Patch Panels	black	10 pieces
418 050	modules KS 1/8 Cat.6, screened, TIA 568-A or -B	metallic	10 pieces
418 051	modules KS 1/8 Cat.5e, screened, TIA 568-A or -B	metallic	10 pieces